

VOE Earl

Multicat

APRIL 15 2025



MAIN SPECIFICATIONS

General

| | |
|-----------------|---|
| Type of vessel: | Multi-Purpose Vessel |
| Classification: | BV 1 ✕ HULL • MACH Tug - Anchor Handling Unrestricted navigation MCA Workboat Category 1 |
| IMO: | 9639983 |
| Callsign: | 2FEP6 |
| MMSI: | 235090599 |
| Flag: | UK |
| Tonnage (UMS): | 199.80 |

Performances

| | |
|----------------------|---------|
| Bollard pull ahead: | 53.30 t |
| Bollard pull astern: | 35 t |

Tank Capacities

| | |
|-------------------|---------------------|
| Fuel oil: | 120 m ³ |
| Fresh water: | 51 m ³ |
| Black/grey water: | 7.30 m ³ |
| Ballast water: | 30 m ³ |
| Dirty oil: | 3.60 m ³ |

Dimensions

| | |
|----------------------|---------------------|
| Length O.A.: | 24.07 m |
| Beam O.A.: | 12.97 m |
| Draught aft (range): | 3.70 m – 4 m |
| Clear deck area: | 180 m ² |
| Deck loading: | 10 t/m ² |

JIFMAR GROUP

→ Contact: sales@jifmar.net



This document is for guidance and information only. Information provided is given under good faith and is non-contractual. This document may be updated without advanced notice. It may not be published, redistributed or reproduced without the prior written consent of ©Jifmar Group.



DETAILED SPECIFICATIONS

Propulsion System

| | |
|----------------|--------------------------------|
| Bow thrusters: | 2 x Kalkman 257 kW in pushbows |
| Main engines: | 2 x Caterpillar 3512C |
| Power output: | 2850 kW |

Auxiliary Systems

| | |
|-----------------|---|
| Generator sets: | 2 x Caterpillar C4.4 107 kVA each 1 x Caterpillar C32 970 kW |
| Harbour set: | 1 x Caterpillar C4.4 60 KVA |

Deck Lay-out

| | |
|------------------------|--|
| Crane FWD: | 1 x Effer 200 000 4s, 9.95 t @ 16 m |
| Crane AFT: | 1 x Effer 200 000 4s, 8.95 t @ 16 m |
| Anchor handling winch: | 100 t pull, 125 t brake, 150 m X 48 mm |
| Towing winch: | 50 t pull, 125 t brake, 700 m X 48 mm |
| Tugger winches: | 4 x 13 t pull 50 m x 22 mm |
| Towing hook: | Mampaey 45 t |
| Stern roller: | 60 t SWL 2 m, Ø 760 mm |
| Bow roller: | 100 t SWL 6 m, Ø 1200 mm |
| Capstan: | WK 5 t |

Accommodation

| | |
|---------|----------------------|
| POB: | 8 Cat 2 / 6 Cat 1 |
| Cabins: | 2 single 2 double |

Navigation & Communication

| | |
|--------------------------|----------|
| GMDSS: | A1 + A2 |
| Satellite communication: | Starlink |

ADDITIONAL PICTURES





GENERAL ARRANGEMENT

